



8100 SERIES ZERO SPEED SWITCH - EXPLOSION PROOF

INTERNALLY GEARED FOR SLOW SPEED APPLICATIONS (0.5 TO 25 RPM)

Speed Switch Input - R.P.M i.e. Application Running Speed		Approx. Contact Operating Speeds (R.P.M.)			MOUNTING STYLES			Electro-mechanical rotary motion controls requiring no electrical input. NEMA 7/9 Explosion Proof Housing Approximate ship weight: 13 lbs.			
					Type B - Base Mount						
		Start-Up Trip-Point Upon Initial Speed Switch Acceleration	Drop-Out Point On Shaft Speed Loss		CONTACTS						2015 END USER PRICING - U.S. \$
S.P.D.T. Single Pole Double Throw	D.P.D.T. Double Pole Double Throw				S.P.D.T.(2) Direction Indicating	8121	81212	8131			
MIN	MAX	SLOW LOSS	RAPID LOSS	MODEL NUMBER			EP	EP	EP		
1.5	5	1.5	0.5	0	8121	81212	8131	NOT FIELD ADJUSTABLE	\$ 1,704	\$ 1,768	\$ 1,751
0.5	2.5	0.5	Approx. 4 Sec. After Shaft Rotation Failure		8121-5	81212-5	8131-5		1,704	1,768	1,751
2	25	1.5	Approx. 3-5 Sec. After Shaft Rotation Failure		8122-5	81222-5	8132-5		1,704	1,768	1,751

AcoustiClean Sonic Horns • Airsweep Systems • Counting Devices • Zero Speed Switches

100 Park Street • Putnam, CT 06260 • 860-928-6551

Toll Free: 800-745-6551 • Fax: 860-928-9450

www.ControlConceptsUSA.com